



SIGENERGY

Home Energy Solution

Let the world enjoy green energy



Sigenergy focuses on developing cutting-edge home and business energy solutions, with products ranging from energy storage systems to solar inverters and EV chargers. Our world-class R&D team of hundreds of top industry experts shares the vision of making the world greener via continuous innovation. With global sales and services, we aim to become our customers' most trusted partner on their journey to a more sustainable future.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.

Sigenergy Australia Pty. Ltd.

www.sigenergy.com

Suite 02 Level 7, 191 Clarence St, Sydney NSW 2000, Australia

CONTENTS

Brand

About SIGENERGY

Product

Residential Solution
Product Portfolio

Trusted Partner

Intelligent Manufacturing
Solar-powered Manufacturing
Quality Assurance
Global cases



ABOUT SIGENERGY

Sigenergy focuses on developing cutting-edge home and business energy solutions, with products ranging from energy storage systems to solar inverters and EV chargers. Our world-class R&D team of hundreds of top industry experts shares the vision of making the world greener via continuous innovation. With global sales and services, we aim to become our customers' most trusted partner on their journey to a more sustainable future.

VISION

Enjoy Green Energy

MISSION
Be a distributed energy pioneer.
Build intelligent energy solutions with superior safety,
ultra simplicity, and outstanding performance.

SIGEN

Safe **I**ntelligent **G**reen **E**fficient **N**ew



SIGENERGY HOME ENERGY SOLUTION

Combining solar, storage and EV charging, Sigenergy offers an all-in-one Home Energy Solution that helps you lower utility bill and reliance on the grid. Simple to install, easy to use, smart & safe all around, our system is versatile and scalable to meet every need.

Let numbers talk
Sigenergy is raising industry standards

15 mins

stackable installation

5 layers

battery protection

280 Ah

long cycle-life battery cell

0 ms

load-side disruption

5 mins

fast commissioning

IP66

SigenStor protection rating

25 kW

fast EV charging at home

1-click

full system diagnosis



Simple



Versatile



Robust



Intelligent





▶ **Sigen Energy Controller**
for solar + energy storage system

▶ **Sigen EV DC Charging Module**
Ready for V2X

▶ **Sigen Battery**


8.0 **5.0**
Energy capacity(kWh)

1 – 6
batteries stackable for each stack

5 kWh – 48 kWh
energy capacity range for each stack

Multiple
systems supported in parallel connection

5-in-One, highly integrated design



Sigenenergy is leading a new way of storing, transferring, and consuming home energy. We provide a genuine all-in-one solar energy storage system, SigenStor. Its unique 5-in-One modular design integrates Solar Inverter, EV DC Charger, Battery PCS, Battery Pack, and EMS into one intelligent home energy system. Simple, robust and versatile, it will be a great addition to your home.

Start small, grow on demand

Controller	x1	x1	x1	x1	x1	x1
Battery	x1	x2	x3	x4	x5	x6
Max. Total Energy Capacity	8 kWh	16 kWh	24 kWh	32 kWh	40 kWh	48 kWh



Sigen Energy Controller

3.0 – 12.0 kW Single Phase

5.0 – 30.0 kW Three Phase

- EMS inside for precise control
- On & off-grid compatibility
- Up to 4 MPP. trackers (three phase)
- DC/AC ratio up to 2 (single phase)
- Multi-source black start
- IP66 system protection rating

Sigen Energy Controller 3.0-12.0 kW Single Phase AU&NZ

SigenStor EC	3.0 SP	5.0 SP	6.0 SP	8.0 SP	10.0 SP	12.0 SP	Units
DC Input (from PV)							
Max PV power	6000	10000	12000	16000	20000	24000	W
Max DC input voltage			600				V
Nominal DC input voltage			350				V
Start-up voltage			100				V
MPPT voltage range			50 - 550				V
Number of MPP trackers	2	2	2	3	4	4	
Number of PV strings per MPPT			1				
Max input current per MPPT			16				A
Max short-circuit current per MPPT			20				A
AC Output (on-grid)							
Nominal output power	3000	4999	6000	8000	9999	12000	W
Max output apparent power	3300	4999	6600	8800	9999	12000	VA
Nominal output current	13.6	21.7	27.3	36.4	43.4	54.6	A
Max output current	15.0	21.7	30.0	40.0	43.4	54.6	A
Nominal output voltage		220 / 230 / 240			220 / 230		V
Nominal grid frequency			50 / 60				Hz
Power factor			0.8 leading - 0.8 lagging				
Total current harmonic distortion			THDI < 2%				
Efficiency							
Max efficiency	98.0%	98.0%	98.0%	97.6%	97.6%	97.6%	
European efficiency	97.0%	97.4%	97.4%	97.0%	97.0%	97.0%	
AC Output (backup)							
Nominal output power	3000	5000	6000	8000	10000	12000	W
Max output apparent power	3300	5500	6600	8800	11000	13200	W
Peak output power (10 seconds)	4500	7500	9000	12000	15000	18000	W
Nominal output current	13.6	22.7	27.3	36.4	45.5	54.6	A
Max output current	15.0	25.0	30.0	40.0	50.0	60.0	A
Peak output current (10 seconds)	20.5	34.1	40.9	54.5	68.2	81.8	A
Nominal output voltage		220 / 230 / 240			220 / 230		V
Nominal output frequency			50 / 60				Hz
Power factor			0.8 leading - 0.8 lagging				
Total voltage harmonic distortion			THDv < 2%				
Disruption time of backup switch ¹			0				ms
Battery Connection							
Battery module models			SigenStor BAT 5.0 / 8.0				
Number of modules per controller			1 - 6				pcs
Battery module voltage range			300 - 600				V
Protection							
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection						
General Data							
Dimensions (W / H / D)	700 / 300 / 245		700 / 300 / 260				mm
Weight	18		36				kg
Storage temperature range			-40 ~ 70				°C
Operating temperature range			-30 ~ 60				°C
Relative humidity range			0% ~ 95%				
Max operating altitude			4000				m
Cooling	Natural convection		Smart air cooling				
System ingress protection rating			IP66				
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)						
Standard Compliance							
Standard ³	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477, IEC/EN 61000-6-1, IEC/EN 61000-6-2						

- This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- For all standards refer to the certificates category on the Sigenenergy website.

Sigen Energy Controller 5.0-30.0 kW Three Phase AU&NZ

SigenStor EC	5.0 TP	10.0 TP	15.0 TP	20.0 TP	25.0 TP	30.0 TP	Units
DC Input (from PV)							
Max PV power	8000	16000	24000	32000	40000	48000	W
Max DC input voltage			1100				V
Nominal DC input voltage			600				V
Start-up voltage			180				V
MPPT voltage range			160 - 1000				V
Number of MPP trackers	2	3	3	4	4	4	
Number of PV strings per MPPT			1				
Max input current per MPPT			16				A
Max short-circuit current per MPPT			20				A
AC Output (on-grid)							
Nominal output power	5000	9999	15000	20000	25000	29900	W
Max output apparent power	5500	9999	15000	22000	27500	29900	VA
Nominal output current	7.6	14.4	21.7	30.4	38.0	43.3	A
Max output current	8.4	14.4	21.7	33.4	41.8	43.3	A
Nominal output voltage			380 / 400				V
Nominal grid frequency			50 / 60				Hz
Power factor			0.8 leading - 0.8 lagging				
Total current harmonic distortion			THDI < 2%				
Efficiency							
Max efficiency	98.1%	98.3%	98.3%	98.3%	98.3%	98.4%	
European efficiency	96.1%	97.5%	97.9%	97.9%	98.0%	98.0%	
AC Output (backup)							
Nominal output power	5000	10000	15000	20000	25000	30000	W
Max output apparent power	5500	11000	16500	22000	27500	33000	W
Peak output power (10 seconds)	7500	15000	22500	30000	30000	36000	W
Nominal output current	7.6	15.2	22.8	30.4	38.0	45.6	A
Max output current	8.4	16.7	25.1	33.4	41.8	50.1	A
Peak output current (10 seconds)	11.4	22.8	34.2	45.6	45.6	54.7	A
Nominal output voltage			380 / 400				V
Nominal output frequency			50 / 60				Hz
Power factor			0.8 leading - 0.8 lagging				
Total voltage harmonic distortion			THDv < 2%				
Disruption time of backup switch ¹			0				ms
Battery Connection							
Battery module models			SigenStor BAT 5.0 / 8.0				
Number of modules per controller			1 - 6				pcs
Battery module voltage range			600 - 900				V
Protection							
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection						
General Data							
Dimensions (W / H / D)			700 / 300 / 260				mm
Weight	36	36	36	36	36	38	kg
Storage temperature range			-40 ~ 70				°C
Operating temperature range			-30 ~ 60				°C
Relative humidity range			0% ~ 95%				
Max operating altitude			4000				m
Cooling			Smart air cooling				
System ingress protection rating			IP66				
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)						
Standard Compliance							
Standard ³	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2						

- This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
- This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
- For all standards refer to the certificates category on the Sigenenergy website.



Sigen Battery

- Large cell capacity, low voltage & durable
- Multi-layer full battery safety protection
- Visible battery status on mySigen App
- Quick connectors for fast installation
- AI enablement, optimised battery cycle life
- Parallel connections for flexible battery mix

Sigen Battery 5.0 / 8.0 kWh

SigenStor BAT	5.0	8.0	Units
Performance Specification			
Battery type	LiFePO4		
Total energy capacity	5.38	8.06	kWh
Usable energy capacity ¹	5.2	7.8	kWh
Battery modules voltage range	300 - 900		V
Max. charge / discharge power	2500	4000	W
Max. charge / discharge current	7.5	12.0	A
Peak charge / discharge power (10 seconds)	3750	6000	W
General Data			
Weight	55	70	kg
Dimensions (W / H / D)	767 / 270 / 260		mm
Storage temperature range	-25 - 60		°C
Operating temperature range	-20 - 55		°C
Relative humidity range	5% - 95%		
Max. operating altitude	4000		m
Cooling	Natural convection		
System ingress protection rating	IP66		
Installation method	Floor standing / Wall-mounted		
Standard Compliance			
Standard	IEC/EN 60730-1, UN 38.3, IEC/EN 62619, IEC/EN 63056, IEC/EN 62040		

¹ Test conditions: 100% depth of discharge, 0.2C rate charge & discharge averagely at 25°C, at the beginning of life.



Sigen EV DC Charging Module

- V2X ready technology, future proof
- Max. 25 kW bi-directional charging
- 150V ~ 1000V charging, wide EV compatibility
- Charge EV with green solar power
- Remote control on mySigen App
- IP66 system protection, maintenance free

Sigen EV DC Charging Module 12 / 25 kW

SigenStor EVDC ¹	12	25	Units
DC Charging			
Max. charging power of charging port	12.5	25	kW
Max. discharging power of charging port	12.5	25	kW
Operation voltage range	150 - 1000		V
Max. operation current	40	80	A
Charging interface	CCS2		
Protection			
Short-circuit protection	Supported		
Over / Under voltage protection	Supported		
Overload protection	Supported		
Over temperature protection	Supported		
Reverse polarity protection	Supported		
Welded contactor check	Supported		
General Data			
Dimensions (W / H / D)	700 / 270 / 260		mm
Weight ²	37 (5m cable) / 39 (7.5m cable) / 41 (10m cable)		kg
Storage temperature range	-40 - 70		°C
Operating temperature range	-30 - 60		°C
Relative humidity range	5% - 95%		
Max. operating altitude	4000		m
Cooling	Smart air cooling		
System ingress protection rating	IP66		
Integrated charging cable length ³	5 / 7.5 / 10		m
Function			
Authentication	RFID card / App / No authentication		
Application	Bi-directional V2X operation ⁴ , Smart load management		
User interfaces	LED indicator, App, RFID		
Remote function	OTA, Remote diagnostics		
Standard Compliance			
Standard ⁵	EN IEC 61851-1, EN 61851-23, EN IEC 61851-21-2, ETSI EN 303 645		

1. Sigen EV DC Charging Module needs to be used together with Sigen Energy Controller.
2. The net weight includes the CCS2 cable-assembly also, but excludes the exteriors, wall-mounting fixtures and the related attachments.
3. Integrated charging cable length refers to the length of the cable that extends from the Sigen EV DC Charging Module, not the length of the exposed cable.
4. V2X functionality is limited by the EV's capabilities. Once the relevant standards are published and tested, V2X feature can be upgraded through the OTA. For the official support of vehicle models and support timelines, please refer to future announcement made on the official website.
5. For all standards refer to the certificates category on the Sigenergy website.



SIGENERGY

Sigen Hybrid Inverter

3.0 – 12.0kW Single Phase

5.0 – 30.0kW Three Phase

- Battery ready, future proof
- DC/AC ratio up to 2 (single phase)
- Up to 4 MPP. trackers (three phase)
- IP66 protection rating

Signen Hybrid Inverter 3.0-12.0 kW Single Phase AU&NZ

Signen Hybrid	3.0 SP	5.0 SP	6.0 SP	8.0 SP	10.0 SP	12.0 SP	Units	
DC Input								
Max. PV power	6000	10000	12000	16000	20000	24000	W	
Max. DC input voltage				600				V
Nominal DC input voltage				350				V
Start-up voltage				100				V
MPPT voltage range				50 - 550				V
Number of MPP trackers	2	2	2	3	4	4		
Number of PV strings per MPPT				1				
Max. input current per MPPT				16				A
Max. short-circuit current per MPPT				20				A
AC Output (on-grid)								
Nominal output power	3000	4999	6000	8000	9999	12000	W	
Max. output apparent power	3300	4999	6600	8800	9999	12000	VA	
Nominal output current	13.6	21.7	27.3	36.4	43.4	54.6	A	
Max. output current	15.0	21.7	30.0	40.0	43.4	54.6	A	
Nominal output voltage	220 / 230 / 240					220 / 230	V	
Nominal grid frequency				50 / 60				Hz
Power factor				0.8 leading - 0.8 lagging				
Total current harmonic distortion				THDi < 2%				
Efficiency								
Max. efficiency	98.0%	98.0%	98.0%	97.6%	97.6%	97.6%		
European efficiency	97.0%	97.4%	97.4%	97.0%	97.0%	97.0%		
Additional Features								
Compatible battery module				SignenStor BAT 5.0 / 8.0				
Number of modules per controller				1 - 6				pcs
Battery module voltage range				300 - 600				V
Off-grid peak output power (10 seconds)	4500	7500	9000	12000	15000	18000	W	
Off-grid peak output current (10 seconds)	20.5	34.1	40.9	54.5	68.2	81.8	A	
Nominal output voltage	220 / 230 / 240					220 / 230	V	
Protection								
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection							
General Data								
Dimensions (W / H / D)	700 / 300 / 268			700 / 300 / 283			mm	
Weight	18			36			kg	
Storage temperature range				-40 - 70			°C	
Operating temperature range				-30 - 60			°C	
Relative humidity range				0% - 95%				
Max. operating altitude				4000			m	
Cooling	Natural convection			Smart air cooling				
Ingress protection rating				IP66				
Installation method				Wall-mounted				
Communication	WLAN / Fast Ethernet / RS485 / Signen CommMod (4G/3G/2G)							
Standard Compliance								
Standard ¹	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477, IEC/EN 61000-6-1, IEC/EN 61000-6-2							

¹ This is an optional feature only supported in certain models, please contact Signenergy for more information.
² For all standards refer to the certificates category on the Signenergy website.

Signen Hybrid Inverter 5.0-30.0 kW Three Phase AU&NZ

Signen Hybrid	5.0 TP	10.0 TP	15.0 TP	20.0 TP	25.0 TP	30.0 TP	Units	
DC Input								
Max. PV power	8000	16000	24000	32000	40000	48000	W	
Max. DC input voltage				1100				V
Nominal DC input voltage				600				V
Start-up voltage				180				V
MPPT voltage range				160 - 1000				V
Number of MPP trackers	2	3	3	4	4	4		
Number of PV strings per MPPT				1				
Max. input current per MPPT				16				A
Max. short-circuit current per MPPT				20				A
AC Output (on-grid)								
Nominal output power	5000	9999	15000	20000	25000	29900	W	
Max. output apparent power	5500	9999	15000	22000	27500	29900	VA	
Nominal output current	7.6	14.4	21.7	30.4	38.0	43.3	A	
Max. output current	8.4	14.4	21.7	33.4	41.8	43.3	A	
Nominal output voltage				380 / 400				V
Nominal grid frequency				50 / 60				Hz
Power factor				0.8 leading - 0.8 lagging				
Total current harmonic distortion				THDi < 2%				
Efficiency								
Max. efficiency	98.1%	98.3%	98.3%	98.3%	98.3%	98.4%		
European efficiency	96.1%	97.5%	97.9%	97.9%	98.0%	98.0%		
Additional Features								
Compatible battery module				SignenStor BAT 5.0 / 8.0				
Number of modules per controller				1 - 6				pcs
Battery module voltage range				600 - 900				V
Off-grid peak output power (10 seconds)	7500	15000	22500	30000	30000	36000	W	
Off-grid peak output current (10 seconds)	11.4	22.8	34.2	45.6	45.6	54.7	A	
Nominal output voltage				380 / 400				V
Protection								
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection							
General Data								
Dimensions (W / H / D)				700 / 300 / 283			mm	
Weight	36	36	36	36	36	38	kg	
Storage temperature range				-40 - 70			°C	
Operating temperature range				-30 - 60			°C	
Relative humidity range				0% - 95%				
Max. operating altitude				4000			m	
Cooling				Smart air cooling				
Ingress protection rating				IP66				
Installation method				Wall-mounted				
Communication				WLAN / Fast Ethernet / RS485 / Signen CommMod (4G/3G/2G)				
Standard Compliance								
Standard ¹	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2							

¹ This is an optional feature only supported in certain models, please contact Signenergy for more information.
² For all standards refer to the certificates category on the Signenergy website.



Sigen Energy Gateway

- Seamless switch to backup mode, worry-free energy usage
- Ready for generator, heat pump or other controllable loads
- Support both whole home backup & partial home backup
- 350 ms reverse power flow protection of grid & generator
- Uninterrupted power supply through PV+ESS/grid/generator

Sigen Energy Gateway for AU&NZ

Sigen Gateway	SP AU	TP AU	Units
Grid Connection			
Grid connection type	Single phase	Three phase	
Nominal AC input / output voltage	220 / 230 / 240	380 / 400	V
Nominal AC input / output current	54.6	91.2	A
Nominal AC input / output power	12	60	kW
Nominal AC frequency		50 / 60	Hz
Disruption time of backup switch ¹		0	ms
AC Output to Backup Port			
Nominal AC output voltage	220 / 230 / 240	380 / 400	V
Nominal AC output current	54.6	91.2	A
Nominal AC output power	12	60	kW
Nominal AC frequency		50 / 60	Hz
Overvoltage category		III	
AC Output to Non-Backup Port			
Nominal AC output voltage	220 / 230 / 240	-	V
Nominal AC output current	54.6	-	A
Nominal AC output power	12	-	kW
Nominal AC frequency	50 / 60	-	Hz
Inverter Connection			
Nominal AC voltage	220 / 230 / 240	380 / 400	V
Nominal AC input current	54.6 (INV1), 32 (INV2) ²	45.6 (INV1), 45.6 (INV2), 30 (INV3) ³	A
Compatible EV charger power	7	11 / 22	kW
Smart Port Connection			
Generator output voltage	220 / 230 / 240	380 / 400	V
Nominal input / output current	54.6	91.2	A
Nominal AC input / output power	12	60	kW
Generator 2-wire start		Supported	
General Data			
Dimensions (W / H / D)	495 / 370 / 165	510 / 750 / 179	mm
Weight	12	23	kg
Storage temperature range		-40 ~ 70	°C
Operating temperature range		-30 ~ 55	°C
Relative humidity range		0% ~ 95%	
Max. operation altitude		4000	m
Cooling		Natural convection	
Ingress protection rating		IP54	
Communication		Fast Ethernet , RS485, dry contact	
Installation method		Wall mounted	

- ¹ This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: in the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the backup loads.
- ² For Sigenergy single phase inverter products, 8.0-12.0 kW inverters should be connected to the INV1 port, 3.0-6.0 kW inverters should be connected to the INV2 port. The sum of the parallel power of the Sigenergy inverters cannot exceed 12 kW.
- ³ For Sigenergy three phase inverter products, the INV1 and INV2 ports support 17.0-30.0 kW inverter, the INV3 port supports 6.0-15.0 kW inverter. The sum of the parallel power of the Sigenergy inverters cannot exceed 60 kW.



Sigen Communication Module

- IP66 protection rating, more reliable
- Plug & play, easy to use
- Support 2G / 3G / 4G communication

Sigen Communication Module

	Sigen CommMod	Units
Connection interface	USB	
Installation type	Plug-and-play	
Display	LED indicators	
Dimensions (W / H / D)	52 / 112 / 33	mm
Weight	90	g
Ingress protection rating	IP66	
Power consumption (typical)	< 4	W
Supported standards	4G: FDD-LTE / TDD-LTE 3G: WCDMA / HSDPA / HSUPA / HSPA+ 2G: GSM / GPRS / EDGE3	
Storage temperature range	-40 - 70	°C
Operating temperature range	-30 - 60	°C
Relative humidity range	0% - 95%	
Max. operating altitude	4000	m
Controller / Inverter compatibility	Sigen Energy Controller series Sigen Hybrid Inverter series	





Sigen Power Sensor

- 1% high-accuracy power detection for precise control
- LCD real-time info display, easy to operate and check
- Integrate smoothly with Sigenergy devices, no need for setup
- Top class 100 A direct connection in power sensor with built-in CT
- Support export/import limitations and ready for AI evolving
- 100 ms data refresh rate, instantaneous data feed

Sigen Power Sensor

Sigen Sensor ¹	SP-DH	SP-CT120-DH	TP-DH	TP-CT120-DH	Units
Power Supply					
Grid connection type	1P2W		3P3W/3P4W		
AC input voltage range	176 - 276		173 - 480		Vac
Nominal AC frequency			50 / 60		Hz
Max. operating current	100	-	100	-	A
Measurement Accuracy					
Voltage accuracy			0.5%		
Current accuracy			0.5%		
Power accuracy			1%		
Frequency accuracy			0.2%		
Communication					
Interface			RS485		
Baud rate			9600		bps
Protocol			Modbus RTU		
General Data					
Dimensions (W / H / D)	36 / 100 / 63	18 / 118 / 64	72 / 100 / 66	72 / 94.5 / 65	mm
Weight	0.20	0.07	0.32	0.20	kg
Storage temperature range			-40 - 85		°C
Operating temperature range			-30 - 60		°C
Relative humidity range			0% - 90%		
Ingress protection rating			IP51		
Installation method			DIN Rail 35 mm		
CT Accessory					
Number of CT	-	1	-	3	pcs
Cable length of CT	-	1	-	1	m
Inner diameter of CT	-	16	-	16	mm
Weight of CT	-	0.09	-	0.09	kg
Max. operating current of CT	-	120	-	120	A
Standard Compliance					
Standard	EN 61010-1:2010, EN 61010-2-030:2010				

¹ For more models refer to the Sigenergy website.

Sigen EV AC Charger



- Green power charging with Sigenergy home energy solution
- Data tracking & scheduled charging on mySigen App
- Dynamic load management to prevent overload, user-friendly charging*
- Easy installation with less steps and top/bottom entry option
- Integrated residual current failure protection reduces installation costs
- IP65 protection rating, worry-free outdoor usage with easy O&M

* Only works with Sigenergy home energy solution or additional Sigen Power Sensor

Sigen EV AC Charger 7 / 11 / 22 kW


Sigen EVAC	7	11	22	Units
AC Input & Output				
Nominal charging power	7	11	22	kW
Nominal output voltage	1P/N/PE, 220 - 240	3P/N/PE, 220 - 240 / 380 - 415	3P/N/PE, 220 - 240 / 380 - 415	V
Output current range	6 - 32	6 - 16	6 - 32	A
Nominal AC frequency		50 / 60		Hz
Vehicle connection	Type 2 connector / Type 2 socket with shutter			
AC input cable width range	2.5 - 6.0			mm ²
Protection				
Integrated DC fault detection ¹	6			mA
Integrated AC fault detection ¹	30			mA
Flame retardant rating	UL94-5VB			
Over / Under voltage protection	Supported			
Overload protection	Supported			
Over temperature protection	Supported			
PEN protection	Supported			
Randomized charging delay	Supported			
Ground fault protection	Supported			
Surge protection	Supported			
Grounding system	TT, TN, IT			
User Interface & Communication				
Protocol	RS485, Modbus RTU			
Communication	4G / WLAN / Fast Ethernet			
Authentication	RFID card / App / Auto-charge (no authentication)			
Display	LED indicator / App			
Charging mode ²	100% PV charging / Solar boost charging / Fast charging			
Metering	External meter with RS485 / Integrated metering IC			
Dynamic load management ³	Supported			
Phase switching	Supported			
OCPP protocol	OCPP 1.6J ED 2			
General Data				
Dimensions (W / H / D)	234 / 384 / 126			mm
Weight (case B / case C)	4.5 / 6.4			kg
Storage temperature range	-40 - 70			°C
Operating temperature range	-30 - 55			°C
Relative humidity range	5% - 95%			
Max. operating altitude	4000			m
Cooling	Natural convection			
Ingress protection rating	IP65			
Installation method	Wall-mounted			
Application environment	Outdoor / Indoor			
Standby self-consumption	< 3.6			W
Standard charging cable length	5			m
Standard Compliance				
Standard ⁴	EN IEC 61851-1, IEC 62995, EN IEC 61851-21-2, ETSI EN 300 330 V2.1.1, ETSI EN 301 511 V12.5.1, EN IEC 62311, EN50665, ETSI EN 300 328 V2.2.2			

1. Residual direct current protective device (RDC-PD) with integrated AC pulsating DC and 6mA DC detection, evaluation and mechanical switching in the Sigen EV AC Charger is tested according to IEC 62955.
2. This function needs to be used with SigenStor.
3. This function needs to be used with Sigen Power Sensor.
4. For all standards refer to the certificates category on the Sigenergy website.

mySigen App

Intelligent energy management within touches
For homeowners

Smarter energy life empowered by mySigen App



Real-time monitoring

Energy data refresh every 10 seconds
Visible energy flow & related devices
Auto. system network display on App



AI Mode

Provide intelligent optimization suggestions on system mode, battery capacity and energy usage




Sigen Shield

Discover industry-leading battery safety features



Fun ambient lighting

Customizable lighting language
Add personality to your system



Sigen AI

After-sales engineer
Home energy analyst
Device mgmt. assistant



Interactive services




AI-integrated service interface
Self-diagnosis to identify problems
Submit service requests via the App

*The interface may change after the mySigen App version is updated, please refer to the actual interface.

mySigen App

Intelligent energy management within touches
For installers

Simplify your installation process, one App does it all



*The interface may change after the mySigen App version is updated, please refer to the actual interface.

Leading the Way in Intelligent Manufacturing



6 GWh

Battery production capacity

12 GW

Inverter production capacity

Located in the Lin-gang New Area, Shanghai, a hub of world-class enterprises with strong innovative strengths, the 20,000 sqm manufacturing center is equipped with state-of-the-art technology and innovative manufacturing processes that allow us to produce high-quality products with exceptional efficiency. It also features the latest manufacturing execution system (MES) which streamlines our operations and enables real-time monitoring of the production process.



Runs on Solar by Sigenergy solutions for a Sustainable Tomorrow

By adopting Sigenergy products and embracing solar energy, our factory has realized green manufacturing. With a 3,000 sqm PV plant on the rooftop, We have significantly reduced our reliance on fossil fuels and effectively cut carbon footprint during the manufacturing process. Our solar-powered production also translates into better efficiency and higher cost savings for our business. We are proud to be making a positive impact on the environment, and are committed to continuing to lead our sustainability practices to help build a better world for future generations.


Plant Size


 3,000 m²  362 kW_p  240 kW_{ac}  432 kWh

Estimated Annual Generation

 398,200 kWh

Community Contribution per Year

 309t CO₂ emission reduced

 269 equivalent of trees planted



Where Quality Meets Perfection

At Sigenergy, our unwavering commitment to putting the customer first is at the core of everything we do. We firmly believe that delivering top-quality products is paramount to ensuring customer satisfaction and building long-term relationships. With a relentless pursuit of excellence, we constantly strive to develop innovative products that meet and exceed customer expectations. Our strict implementation of rigorous quality control guarantees that every product leaving our factories is of the highest standard. Moreover, we never settle for complacency; Instead, we embrace a culture of continuous improvement to constantly enhance our products and surpass industry standards.



Manufacturing Execution System (MES)

Quality and efficiency is consistently guaranteed by our MES system, which monitors, tracks, documents, and controls the entire manufacturing process from raw materials to finished products, as well as full product lifecycle management.



Powering Homes Worldwide

From Snowy Scandinavia to Warm Oceania



From the coldest **-20°C** to the hottest **48°C**,
From the **Coast** to the **Outback**,
From **Metro** homes to **Country** farms

SigenStor operates perfectly in any climate, from Nordic Winter to Aussie Summer. Whether installed indoor or outdoor, on-grid or off-grid, SigenStor offers flexibility and reliability in a wide range of scenarios. Whether you want to cut electricity bills, reduce reliance on diesel generators, or back up the whole house during power outages, 5-in-One SigenStor is here to meet your needs.

